5mp 4 Kanal XVR, HD-TVI CVI AHD CVBS IP-CAM



5mp 4 Kanal XVR, HD-TVI CVI AHD CVBS IP-CAM

De?erlendirme:Henüz de?erlendirilmemi?
Fiyat
Çe?it fiyat? belirleyici :

Vergi dahil taban fiyat7.615,12 TL

?ndirimli fiyat6.453,49 TL

?ndirimli sat?? fiyat?

Sat?? fiyat? 7.615,12 TL

Vergi hariç sat?? fiyat? 6.453,49 TL

?ndirim

Vergi tutar?1.161,63 TL

Bu ürün hakk?nda soru sorun

ÜreticiNetVISION

Aç?klama

MODEL:NV-XVRD421 MARKA:NETVISION

TEKN?K ÖZELL?KLER	
DIY Video Giri? formatlar?	DIY Video Input: HD includes AHD, HD?CVI, HD?TVI
Kamera Türüne Göre Kay?t Kanal? Say?s?	HD: Max 4CH@30fps / IPC: Max 16CH@30fps / Analog: Max 4CH@30fps
Video Ç?k???	Video Output: 1xHDMI (Max. 2K) /1xVGA /1xCVBS
Ses Giri?i/Ç?k???	Audio Input/Output: RCA 4CH In/ 1CH Out
S?k??t?rma Metodu	Compression Method: H.264
Desteklenen Kamera Tür ve Çözünürlükleri:	
AHD/TVI:5MP	AHD/TVI: 5M, PAL every channel 1fps?12fps adjustable; NTSC every channel 1fps?12fps adjustable;
AHD/TVI:4MP	AHD/TVI: 4M, PAL every channel 1fps?15fps adjustable; NTSC every channel 1fps?15fps adjustable;
AHD/TVI:3MP	AHD/TVI: 3M, PAL every channel

	1fps?18fps adjustable; NTSC every channel 1fps?18fps adjustable;
HD:1080P/720P	HD: 1080P/720P, PAL every channel 1fps?25fps adjustable; NTSC every channel 1fps?30fps adjustable;
Analog:960	Analog: 960H, PAL every channel 1fps?25fps adjustable; NTSC every channel 1fps?30fps adjustable;
IP KAMERA:8MP/6MP/5MP/4MP/3MP/2MP/1MP	IPC: 8MP/6MP/5MP/4MP/3MP/2MP/1MP, etc (Total incoming bandwidth ?80M),
Sistemi PAL, Her kare 1-25fps aras? ayarlanabilir.	PAL every channel 1fps?25fps adjustable; NTSC every channel 1fps?30fps adjustable;
?zleme Çözünürlü?ü:5M/4M/3M/1080P/720P	Preview resolution: 5M/4M/3M/1080P/720P
Kay?t izleme:tek /dörtlü kanal modunu destekler	Playback: Support single channel/four channels mode
Hexaplex e?zamanl? çal??ma fonksiyonu: Canl? izleme,kay?t yapma,Kay?t izleme,Network i?lemleri	Hexaplex operation simultaneously: Live, Recording, Playback, Network Operating
Statik,Dinamik IP, DDNS,P2P,interne explorer ve Özel CMS	Static, Dynamic IP and DDNS, P2P, Support IE and special client software
Arayüz araçlar? I/O	2×USB ; 1xRS485; 1xRJ45(10M/100M adaptive Ethernet interface)
HDD	1 SATA Hard Disk interface (2.5"/3.5" SATA, Up to 6TB)
HDMI,VGA,USB,SES, Yedek alma:USB2,0 veya Network ortam?	Backup: USB2.0 (such as U disk, USB drive) and Network
Mobil izleme:IPHONE,IPAD,ANDROID	Support remote view by Mobilephone (iPhone, iPad, Android Phone)
Güç tüketimi 12v dc 6wat (disksiz)	Power consumption: DC 12V ?10W (Without Hard Disk)
Boyutlar:	Dimensions (L×W×H): 260*215*43(mm) Weight: 2kg

Yorumlar

Bu ürün için henüz bir yorum yap?lmam??.